



TOWN of MOORESVILLE

4 East Harrison Street

Mooresville, Indiana 46158

Telephone (317) 831-9547
Public Works Department
Dave Moore, Superintendent

The following streets shall be milled to a depth of one and a half inches from the curb or the edge of the road for three feet and tapered to zero inches. They shall be tacked and overlaid with 1½ inches of 9.5 millimeter HAC surface material. Each connected street shall be milled and inset to the opposite side of the parallel side walk or 20 feet if no walk is present.

1. Honeysuckle Drive: From Bridge Street south to the new pavement seams.
2. Honeysuckle Court: Including the cul-de-sac.
3. Cottonwood Court: Including the cul-de-sac.
4. The ally between Indiana Street and Maple Lane from Washington Street to Lincoln Lane.
5. Circle Drive: Including cul-de-sac.
6. Town Center Drive North.
7. Washington Street between Jefferson Street and Monroe Street.

Old State Road 67 from the State Maintained Area going south to the County maintained area or new asphalt seams, including the Town maintained DE cell lanes, shall be milled at all intersections at a depth of one and a half inches to provide a smooth transitions. These shall also be tacked and overlaid with 1½ inches of 9.5 millimeter HAC surface.

These streets shall all be tacked and overlaid with 1 ½ inches of 9.5 millimeter HAC surface.

1. Merriman Road between Old State Road 67 and State Road 67
2. Lewis Drive
3. Center Drive

Ally west of Harlan Drive from Samuel Moore to Bridge Street to be milled 1 ½ inches, tacked and overlaid with 1 ½ inches of 9.5 millimeter HAC surface.

All adjoining or intersecting streets shall be milled 20 feet inward if there is no walk or to the back side of the parallel sidewalk which will eliminate seams in drainage channels.

No Recycled materials will be accepted or used for this project.

The Town of Mooresville has the right to increase or decrease up to 25% of quantities.

Millings not requested by the town shall be hauled away.